



DESCRIPTION

Replace existing metal halide flood fixtures with these more efficient color selectable LED flood fixtures.

FEATURES

- Delivers up to 144 LPW for highly efficient performance
- Yoke mount adjusts up to 180° (90° up and 90° down)
- Slipfitter adjusts up to 180° (90° left and 90° right)
- Combination yoke and slipfitter mount adjusts to virtually any up or down degree aiming angle desired
- 0-10V dimming; see Dimmer Compatibility for list of compatible dimmers
- 11.81" whip
- Light output changes depending on the color temperature selected; see Selectable Table for full breakdown
- Color temperature can be adjusted using the dip switch on the top of the fixture; see installation instructions for more information

LISTINGS

- UL rated for wet locations
- IP65
- FCC
- DesignLights Consortium® 5.1 Premium - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN: PLTSNH251Y5[1;2;Blank][1;Blank][1;3;2;4]

PERFORMANCE

- CRI: >80
- CCT: 3000K, 4000K, 5000K
- Rated lifetime L70: 100,000 hours

THERMAL

- -31°F to 122°F or (-35°C to 50°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Surge Protection: 4Kv
- Dimmable power supply (0-10V)

INSTALLATION

- Designed for installation with included slipfitter mount; see installation instructions.

CONSTRUCTION

- Die-cast aluminum housing
- Durable polyester bronze powder coating withstands demanding environments
- Clear impact-resistant tempered glass lens

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Safety and Security Lighting
- Sign Lighting
- Building Facades

PERFORMANCE SUMMARY

Item #	Watts*	CCT*	Beam Angle	CRI	Dimming	Voltage	Replaces	Mounting	BUG	DLC #	DLC Level
PLT-13240	80W	3000/ 4000/ 5000	145°	>80	0-10V	120-277V	250W MH	Slipfitter	B3-U0-G1	PLTSNH251Y5[1;2;Blank] [1;Blank][1;3;2;4]	5.1 Premium

*See Selectable Table for full breakdown

SELECTABLE TABLE

Wattage	CCT	Lumen	Efficacy
80	3000K	10,712	134
	4000K	11,509	144
	5000K	11,325	142

DIMMER COMATIBILITY

Brand	Model
Leviton	SD710
Leviton	IP710
Legrand	RH4FBL3PW
Lutron	NFTV
Lutron	NTSTV
Lutron	DVTV

DIMENSIONS



DIMENSIONS

Length – 7.4"
 Length (with mount) – 16"
 Width – 10.5"
 Depth – 3"
 Weight – 4.10 lbs
 Weight (w/ mount) – 6.88 lbs

Slipfitter Length – 12.91"
 Slipfitter Width – 10.24"
 Slipfitter Height – 2.87"

PHOTOMETRICS

