

DesignLights Consortium



Model Number	PLTSPJ136
Classification	Standard
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)
Reported Input Wattage	13 W
Reported Light Output	1570 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-6DD767
DLC Family Code	EMWBQW
Listing Status	Listed
Date Qualified	2024-05-28

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-6DD767
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTSPJ136
Parent	Yes
Classification	Standard
DLC Family Code	EMWBQW
Length	3.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T8 Three-Foot
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming above 10%
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	TYPEA:Dimmable depending on ballast capability TYPEB:Input Signal from External Control Source
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	210 °
Reported Light Output	1570 lm
Reported Efficacy (AC)	121 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	0
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-11
Reported Minimum Light Output	1570 lm
Reported Maximum Light Output	1570 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	6500 K
Reported Default Light Output	1570 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	13 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	13 W
Reported Maximum Input Wattage	13
Reported Default Input Wattage	13 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	277
Tested Light Output	1652 lm
Tested Efficacy (AC)	127.1 lm/W
Tested CCT	3072 K
Tested CRI (Ra)	83
Tested R9	6
Tested IES Rf	85
Tested IES Rg	97
Tested IES Rcs,h1	-11 %
Tested Duv	0.0008
Tested Beam Angle	213 °

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	13 W
Tested Total Harmonic Distortion	13.9 %
Tested Power Factor	0.951

VERSION HISTORY VIEW DETAILS

2024-05-28	Listed	5.1	Standard
------------	--------	-----	----------