# **DesignLights Consortium**





| Model Number           | PLTM15A512                                                  |  |  |
|------------------------|-------------------------------------------------------------|--|--|
| Classification         | Premium                                                     |  |  |
| Primary Use            | High-Bay Luminaires for Commercial and Industrial Buildings |  |  |
| Reported Input Wattage | 130 W                                                       |  |  |
| Reported Light Output  | 17680 lm                                                    |  |  |
| Reported CCT           | 5000 K                                                      |  |  |
| Reported CRI (Ra)      | 80                                                          |  |  |
| Product ID             | S-5MGHVB                                                    |  |  |
| DLC Family Code        | <u>EMWBFE</u>                                               |  |  |
| Listing Status         | Listed                                                      |  |  |
| Date Qualified         | 2023-08-21                                                  |  |  |

#### **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting                  |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1                                   |
| Product ID                     | S-5MGHVB                              |
| Manufacturer                   | Precision Lighting & Transformer, Inc |
| Brand                          | PLT                                   |
| Model Number                   | PLTM15A512                            |
| Parent                         | Yes                                   |
| Classification                 | Premium                               |
| DLC Family Code                | EMWBFE                                |
| Input Power Type               | AC                                    |

#### PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Luminaires                                           |  |
|-------------------------|-------------------------------------------------------------|--|
| General Application     | High-Bay                                                    |  |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |  |

#### **CONTROL FEATURES VIEW DETAILS**

| Integral Controls                      | Yes                                 |
|----------------------------------------|-------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below  |
| Integral Control Capability            | No                                  |
| Sensor Type                            | Daylight Sensing, Occupancy Sensing |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                        |
| SSL V5 Wireless Communication Protocol | No                                  |
| Field Adjustable Light Output          | No                                  |
| White-Tunable                          | No                                  |
| Warm-Dimming                           | No                                  |
| Field Adjustable Light Distribution    | No                                  |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 17680 lm |
|-------------------------------|----------|
| Reported Efficacy (AC)        | 136 lm/W |
| Reported CCT                  | 5000 K   |
| Reported CRI (Ra)             | 80       |
| Reported R9                   | -13      |
| Reported IES Rf               | 81       |
| Reported IES Rg               | 92       |
| Reported IES Rcs,h1           | -15      |
| Reported Default Light Output | 17680 lm |

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 130 W     |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 8.2 %     |
| Reported Power Factor              | 0.979     |
| Reported Default Input Wattage     | 130 W     |
| Voltage Range                      | 120-277 V |

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Tested Voltage for Minimum Efficacy | 120         |
|-------------------------------------|-------------|
| Tested Light Output                 | 17315 lm    |
| Tested Efficacy (AC)                | 141.77 lm/W |
| Tested CCT                          | 5093 K      |
| Tested CRI (Ra)                     | 80          |
| Tested R9                           | -13         |
| Tested IES Rf                       | 81          |

| Tested IES Rg     | 92     |
|-------------------|--------|
| Tested IES Rcs,h1 | -15 %  |
| Tested Duv        | 0.0028 |

## **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Tested Input Wattage             | 122.1 W |
|----------------------------------|---------|
| Tested Total Harmonic Distortion | 8.2 %   |
| Tested Power Factor              | 0.979   |

## **VERSION HISTORY VIEW DETAILS**

| 2023-08-21 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|------------|--------|-----|---------|