# **DesignLights Consortium**





| Model Number           | PLTM16B322  |
|------------------------|---|
| Classification         | Premium   |
| Primary Use            | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 170 W   |
| Reported Light Output  | 23120 lm  |
| Reported CCT           | 5000 K  |
| Reported CRI (Ra)      | 79  |
| Product ID             | S-SRBFXD  |
| DLC Family Code        | <u>MMMTEB</u>   |
| Listing Status         | Listed  |
| Date Qualified         | 2024-01-11  |

#### **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting                  |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1                                   |
| Product ID                     | S-SRBFXD                              |
| Manufacturer                   | Precision Lighting & Transformer, Inc |
| Brand                          | PLT                                   |
| Model Number                   | PLTM16B322                            |
| Parent                         | Yes                                   |
| Classification                 | Premium                               |
| DLC Family Code                | MMMTEB                                |
| Input Power Type               | AC                                    |

#### PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Luminaires   |  |
|-------------------------|---|--|
| General Application     | High-Bay  |  |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |  |

#### **CONTROL FEATURES VIEW DETAILS**

| Integral Controls                      | No                                 |
|--|------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No                                 |
| Sensor Type                            | No                                 |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No                                 |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | No                                 |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 23120 lm |
|-------------------------------|----------|
| Reported Efficacy (AC)        | 136 lm/W |
| Reported CCT                  | 5000 K   |
| Reported CRI (Ra)             | 79       |
| Reported R9                   | -15      |
| Reported IES Rf               | 81       |
| Reported IES Rg               | 94       |
| Reported IES Rcs,h1           | -15      |
| Reported Default Light Output | 23120 lm |

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 170 W     |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 17.8 %    |
| Reported Power Factor              | 0.98      |
| Reported Default Input Wattage     | 170 W     |
| Voltage Range                      | 120-277 V |

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Tested Voltage for Minimum Efficacy | 120         |
|-------------------------------------|-------------|
| Tested Light Output                 | 23340 lm    |
| Tested Efficacy (AC)                | 141.82 lm/W |
| Tested CCT                          | 5038 K      |
| Tested CRI (Ra)                     | 79          |
| Tested R9                           | -15         |
| Tested IES Rf                       | 81          |

| Tested IES Rg     | 94    |
|-------------------|-------|
| Tested IES Rcs,h1 | -15 % |
| Tested Duv        | 0.002 |

# **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Tested Input Wattage             | 163.1 W |
|----------------------------------|---------|
| Tested Total Harmonic Distortion | 17.8 %  |
| Tested Power Factor              | 0.976   |

## **VERSION HISTORY VIEW DETAILS**

| 2024-01-11 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|------------|--------|-----|---------|