

DesignLights Consortium



| | |
|------------------------|--|
| Model Number | PLTSN541[1;2;3]2[1;2;3;blank][1;2;3;4;5;blank] |
| Classification | Premium |
| Primary Use | Outdoor Full-Cutoff Wall-Mounted Area Luminaires |
| Reported Input Wattage | 77.3 W |
| Reported Light Output | 11335 lm |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 70 |
| Product ID | S-UQEP8I |
| DLC Family Code | SLFAIE |
| Listing Status | Listed |
| Date Qualified | 2023-01-20 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|--|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-UQEP8I |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT Solutions |
| Model Number | PLTSN541[1;2;3]2[1;2;3;blank][1;2;3;4;5;blank] |
| Parent | No |
| Classification | Premium |
| DLC Family Code | SLFAIE |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|--|
| Category | Outdoor Luminaires |
| General Application | High Output |
| Primary Use Designation | Outdoor Full-Cutoff Wall-Mounted Area Luminaires |

CONTROL FEATURES VIEW DETAILS

| | |
|--|---------------------------------------|
| Integral Controls | Yes |
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No |
| Sensor Type | Exterior Photocell, Occupancy Sensing |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|-------------|
| Reported Light Output | 11335 lm |
| Reported Efficacy (AC) | 146.69 lm/W |
| Reported CCT | 5000 K |
| Reported CRI (Ra) | 70 |
| Reported R9 | -36 |
| Reported IES Rf | 75 |
| Reported IES Rg | 93 |
| Reported IES Rcs,h1 | -18 |
| Reported Default Light Output | 11335 lm |
| Reported BUG Rating | B4 U0 G0 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 77.3 W |
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Maximum Input Wattage | 77.3 |
| Reported Default Input Wattage | 77.3 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|---|------------------------|
| Field Adjustable Light Distribution Setting | Pointing straight down |
|---|------------------------|

VERSION HISTORY VIEW DETAILS

2023-01-20

Listed

5.1

Premium