

Wood Finish Architectural Light

The wood architectural linear light is the perfect solution for your modern interior lighting, it's easy to combine multiple of the pendants light to create a stylish ambiance. The selectable DIP switches for power, CCT and up and down lighting offers flexibility to achieve precise configuration to fulfill any architectural and light level requirement. Ideal for using in offices, conference rooms, hallways, educational facilities and more.

- Watt and CCT selectable
- PF >0.9
- THD <20%
- IP20, IK08
- 2kV Surge Protection
- 5 years warranty
- Adjustable light distribution
 - ① UP:100% & DOWN:0%
 - ② UP:70% & DOWN:30%
 - ③ UP:50% & DOWN:50%
 - ④ UP:30% & DOWN:70%
 - ⑤ UP:0% & DOWN:100%

Certifications



Down light



Up light



CCT and Wattages Tunable



Model	Watt Selectable	Input Voltage	LPW	Typical Lumen	CCT Selectable	CRI	Dimmable	Max linkable watt	Operating Mode	Finish Colour	Dimension (Inch)
PLT-90472	25W/20W/15W/10W	120-277V/ 120-347V	115 Lm/w	2875lm	30K/35K/40K/50K/57K Selectable	83+	0-10V	600W @ 120V 1200W @ 277V	Uplight/ Downlight Selectable	Wood	23.66"x2.2"x3"
PLT-90473	35W/30W/25W/20W			4025lm							35.47"x2.2"x3"
PLT-90474	50W/45W/40W/35W			5750lm							47.28"x2.2"x3"
PLT-90475	100W/90W/75W/60W			11500lm							94.33"x2.2"x3"

Sensor and Emergency backup battery are available via Special Order. call 1-800-624-4488.

DIP Switches for Watt/CCT/Up&Down Light Distribution



CCT Selectable
30K/35K/40K/50K/57K(preset at 50K)

Watt Selectable
2FT: 25W 20W 15W 10W(preset at 25W)
3FT: 35W 30W 25W 20W(preset at 35W)
4FT: 50W 45W 40W 35W(preset at 50W)
8FT: 100W 90W 75W 60W(preset at 100W)



Up&Down Light Distribution
①Up:100%& Down: 0%
②Up: 70% & Down: 30%
③Up: 50% & Down: 50%
④Up: 30% & Down: 70% (preset)
⑤Up: 0% & Down: 100%

Adjustable up&down light distribution(5 positions)



Size	Total Watt	Up	Up Watt	Up Lumen Output	Down	Down Watt	Down Lumen Output
2FT	25W	0%	0W	0	100%	25W	2875lm
		30%	7W	805lm	70%	18W	2070lm
		50%	12.5W	1437.5lm	50%	12.5W	1437.5lm
		70%	18W	2070lm	30%	7W	805lm
		100%	25W	2875lm	0%	0W	0
3FT	35W	0%	0W	0	100%	35W	4025lm
		30%	10.5W	1207.5lm	70%	24.5W	2817.5lm
		50%	17.5W	2012.5lm	50%	17.5W	2012.5lm
		70%	24.5W	2817.5lm	30%	10.5W	1207.5lm
		100%	35W	4025lm	0%	0W	0
4FT	50W	0%	0W	0	100%	50W	5750lm
		30%	15W	1725lm	70%	35W	4025lm
		50%	25W	2875lm	50%	25W	2875lm
		70%	35W	4025lm	30%	15W	1725lm
		100%	50W	5750lm	0%	0W	0
8FT	100W	0%	0W	0	100%	100W	11500lm
		30%	30W	3450lm	70%	70W	8050lm
		50%	50W	5750lm	50%	50W	5750lm
		70%	70W	8050lm	30%	30W	3450lm
		100%	100W	11500lm	0%	0W	0

Accessories

Suspension Mount – Standard



Continuous Run Kit –Optional*



**Continuous run kit available via Special Order. Call 1-800-624-4488.*