DesignLights Consortium





Model Number	PLTM946142		
Classification	Standard		
Primary Use	Direct Linear Ambient Luminaires		
Reported Input Wattage	34 W		
Reported Light Output	4488 lm		
Reported CCT	3500 K		
Reported CRI (Ra)	Ra) 82		
Product ID	S-M4V2B8		
DLC Family Code	ode QQQVXT Listed		
Listing Status			
Date Qualified	2022-12-21		

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-M4V2B8
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM946142
Parent	Yes
Classification	Standard
DLC Family Code	QQQVXT
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Linear Ambient	
Primary Use Designation	Direct Linear Ambient Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4488 lm
Reported Efficacy (AC)	132 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	7
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Minimum Light Output	4488 lm
Reported Maximum Light Output	4488 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4488 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	34 W
Reported Total Harmonic Distortion	7.4 %
Reported Power Factor	0.995
Reported Minimum Input Wattage	34.0 W
Reported Maximum Input Wattage	34
Reported Default Input Wattage	34 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|--|

Tested Light Output	4459 lm
Tested Efficacy (AC)	128.46 lm/W
Tested CCT	3408 K
Tested CRI (Ra)	82
Tested R9	7
Tested IES Rf	83
Tested IES Rg	98
Tested IES Rcs,h1	-12 %
Tested Duv	-0.00077

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	34.7 W
Tested Total Harmonic Distortion	7.4 %
Tested Power Factor	0.952

VERSION HISTORY VIEW DETAILS

2	022-12-21	Listed	5.1	Standard