



Selectable LED High Bay

Save Time, Save Money, Without Compromising Quality

The Ultra Compact LED High Bay (160lm/w high efficacy) is a new generation of eco-friendly luminaire provides maximum light output, exceptional illumination and energy saving.

- Industrial grade compact design
- V-hook and chain mounting accessories included
- Durable prismatic lens delivers high lumen output
- PF > 0.9
- THD < 20%
- 0-10V dimmable
- 5-year warranty

Certifications



Sturdy and Robust Design

Quick and Easy Installation

CCT Tunable

Wattage Tunable

Ambient -20°C to 45°C



Reduces packaging waste by **>75%**




Reduces installation time and labor by **>30%**



Ships with up to **>144** units / pallet



Job Pack



Small Design, Big Savings




Ultra Compact



Typical 2ft High Bay



Motion Sensor Available*



Application

Ultra Compact Size, Full Scale Performance

One to one replacement for typical 2ft high bay

Model	Watt	Input Voltage	LPW	Typical Lumen	CCT	CRI	Dimmable	Dimensions	Installation Height
PLT-90478	100/80/65W Selectable	120-277V	160 lm/w	15846lm	CCT Selectable 4000K/5000K/5700K	>80	0-10V	14.17" x 12.06" x 1.8"	30-35ft

*Optional sensor and emergency battery backup available via Special Order. Call 1-800-624-4488.



Selectable Table

Wattage	CCT	Lumens	LPW
65W	4000K	10,524	162
	5000K	10,515	162
	5700K	10,461	161
80W	4000K	12,659	158
	5000K	12,693	159
	5700K	12,587	157
100W	4000K	15,686	157
	5000K	15,846	158
	5700K	15,668	157