







PLT-13354 -- 480W, 61,546 Lumens, 5000K, Black Finish

- 20-degree Beam Angle
- 277-480V
- Yoke Mount
- Shield Included



DIMENSIONS



Yoke

Slipfitter*

ADVANTAGE

- UL
- Input voltage 277-480Vac
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long lifespan
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury
- Output can be dimmed with 0-10V dimmers.

APPLICATION

- ◆ Gymnasiums;
- ◆ Squares or plazas;
- ◆ Shipyards, Airports, wharfs;
- ◆ High mast and Contour lighting

*Available via Special Order. Call 1-800-624-4488

SPECIFICATIONS


OPTICAL	Input Power (Tolerance : ±10%)	480W		
	Color Temperature	4000K*	5000K	5700K*
	Lumen (Tolerance : ±10%)	61286.4 LM	61546 LM	64785.6 LM
	Efficacy (Tolerance :±3%)	127.68 LM/W	128 LM/W	128.72 LM/W
	CRI	>70		
	Color Consistency	<6 Steps (or <6 SDCM)		
	BUG	B5-U0-G3		
	Distribution Pattern	Field Angle (10%) (Tolerance ±15%): NEMA: 4 (4H4V)		
	Beam Angle (50%) (Tolerance : ±15%)	20°		
ELECTRICAL	Input Voltage and Frequency	277-480VAC, 50/60Hz		
	PF (Tolerance : -3%)	≥0.9		
	THD (Tolerance : +5%)	≤20%		
	Flicker Percent	<5%		
	Driver Brand	UPower Tek		
	Driver Model	TLD-480-C280-ENU		
	Driver Surge protection	L/N-PE: 20kV, L-N:6kV		
	Dimming	0-10V dimming standard		
	Sensor Type	Integral Sensor Receptacle*, Exterior Photocell*		
	Optional Accessory	Sensor Receptacle+Photosensor* /Sensor Receptacle+Short Cap*, Surge-protective Device*		
MATERIALS	LED Brand	Bridgelux		
	LED Type	SMD3030		
	LED QTY	504 PCS		
	Housing	Die-cast aluminum		
	Housing Color	Black, White*, Bronze* or Customized*		
	EPA	1.6 ft²		
	Waterproof Rating	WET (IP65)		
OTHERS	Operating Temperature	-40°C TO 45°C		
	Storage Temperature	-40°C TO 80°C		
	Operating Humidity	20% - 90% RH		
	Storage Humidity	10% - 95% RH		
	Warranty	5 years		

*Optional CCTs, mounts, finishes, and accessories available via Special Order. Call 1-800-624-4488.

PACKAGE

Bracket Type	Carton Size	Qty / Carton	Net Weight / Carton	Gross Weight / Carton
Yoke	505*490*480 MM	1 PC	14.5 KG	16.5 KG
Slipfitter*	505*490*480 MM	1 PC	15.0 KG	17.0 KG

Tolerance of Carton Size: ±15 MM, Tolerance of Weight: ±10%.



NOTICE FOR USER

- Please turn off power before installation or maintenance.
- Verify that supply voltage is correct by comparing it with the luminaire label information. Please make sure the wiring is insulated.
- Installation, service, and maintenance of luminaires should be performed by a qualified licensed electrician.

TROUBLESHOOTING

Problem	Solution
Flickering Light	Turn off the power, then turn on again after 3 minutes. If the light continues to flicker, call a licensed electrician.
Fixture not turning on	Check the electrical connection.