



Product Specification

Document No.:

Version: A0

Page: 1/2

model no. **PLT-50390, PLT-50391, PLT-50392, PLT-50393, PLT-50394**

1. DESCRIPTION:

LAMP TYPE:	PLED
LAMP CLASSIFIED:	Type B, Gen2
BASE TYPE:	G24D(Two Pin-Base)
EQUIVALENT	26W
WATTAGE:	9W
CCT:	2700K,3000K,3500K,4000K, 5000K
DIFFUSER TYPE:	PC
WARRANTY:	5 YEARS



Suitable for dry and damp locations
Suitable for open fixtures
Vertical burn position only

2. PRODUCT FEATURES

Replacement for conventional fluorescent lamp
UL Listed
Environmentally friendly: no mercury

3. PERFORMANCE (If no specified, the test conditions in below items are: Ta=25°C±1°C, RH≤65%, air free.)

3.1 Electrical Characteristics

PARAMETERS	SYMBOL	MIN	RATED	MAX	UNIT	Test Condition
Input voltage	U	--	120/277	--	V	/
Frequency	f	--	50/60	--	Hz	/
Power factor	PF	-3%	0.9	--	/	Vin=120,277Vac
Total Harmonic Distortion	THD	--	20%	+5%	/	Vin=120,277Vac
Starting time	t	--	--	2	s	Vin=120,277Vac
Rated power per lamp (Bare)	Plamp	-10%	9.0	+10%	W	Vin=120,277Vac
Flicker Percent	/	--	--	--	/	/
Dimming Type	/					

3.2 Photometrical Characteristics

PARAMETERS	SYMBOL	MIN	RATED	MAX	UNIT	Test Condition
Beam Angle	/	--	100	--	°	
Flux @2700K	Φ	-10%	900	--	LM	Vin=120,277Vac
Flux @3000K/3500K		-10%	950	--		
Flux @4000K/5000K		-10%	1000	--		
Lamp efficacy@2700K	η	-10%	100	--	LM/W	
Lamp efficacy@3000K/3500K		-10%	106	--		
Lamp efficacy@4000K/5000K		-10%	111	--		

3.3 Color Characteristics (refer to ANSI C78.377-2015)

Chromaticity coordinates

CENTER POINT	CCT=2700K	X=0.4578 Y=0.4101	/
	CCT=3000K	X=0.4338 Y=0.4030	
	CCT=3500K	X=0.4073 Y=0.3917	
	CCT=4000K	X=0.3818 Y=0.3797	
	CCT=5000K	X=0.3447 Y=0.3553	



Product Specification

Document No.:

Version: A0

Page: 2/2

model no. PLT-50390, PLT-50391, PLT-50392, PLT-50393, PLT-50394

PARAMETER	SYMBOL	MIN	RATED	MAX	Unit	Test Condition
Color Render Index	Ra	80	82	--	/	/
R9	R9	0	12	--		
Color tolerance	/	--	--	5	SDCM	

4. LUMEN MAINTENANCE & LIFE

PARAMETERS	SYMBOL	MIN	RATED	MAX	UNIT	Test Condition
Lumen Maintenance at 6000hrs	/	--	95.8%	--	/	/
Life	t	--	50000	--	Hrs	Ta=45C, air free
Warranty	/	--	5	--	Year	Ta=45C, air free

5. OPERATION TEMPERATURE & STORAGE TEMPERATURE

PARAMETERS	SYMBOL	MIN	RATED	MAX	UNIT	Test Condition
Ambient Temperature	T _A	-20	--	45	°C	/
Storage Temperature	T _{st}	-40	--	85		/


6. COMPATIBILITY

N/A

7. APPROBATION COMPLIANCE

UL1993, FCC part 18 no-consumer, RoHS compliance, NSF

8. DIMENSIONS



SYMBOL	MIN	TYP	MAX	UNIT
A	45	--	47	mm
B	45	--	47	mm
C	100	--	103	mm
D	116	--	119	mm

9. Connection & Wiring

WIRING DIAGRAM	WIRING ILLUSTRATION
	/

10. SKUs

PLT-50390 - 9W, 900 Lumens, 100 LPW, 2700K
PLT-50391 - 9W, 950 Lumens, 106 LPW, 3000K
PLT-50392 - 9W, 950 Lumens, 106 LPW, 3500K
PLT-50393 - 9W, 1000 Lumens, 111 LPW, 4000K
PLT-50394 - 9W, 1000 Lumens, 111 LPW, 5000K