

DesignLights Consortium



Model Number	STAKS 2X2 ALO3 SWW7 [All Options, Excluding UVOLT]
Classification	Standard
Primary Use	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	40.92 W
Reported Light Output	5040.8 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	PMBHKDSW
DLC Family Code	UUUCGX
Listing Status	Listed
Date Qualified	2021-05-10

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PMBHKDSW
Manufacturer	Acuity Brands Lighting
Brand	LITHONIA
Model Number	STAKS 2X2 ALO3 SWW7 [All Options, Excluding UVOLT]
Parent	Yes
Classification	Standard
DLC Family Code	UUUCGX
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5040.8 lm
Reported Efficacy (AC)	123.18 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	10
Reported IES Rf	85
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3000 lm
Reported Maximum Light Output	5000 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4000 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40.92 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	26 W
Reported Maximum Input Wattage	40.92
Reported Default Input Wattage	34 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	5040.8 lm

Tested Efficacy (AC)	123.18 lm/W
Tested CCT	3506 K
Tested CRI (Ra)	83
Tested R9	10
Tested IES Rf	85
Tested IES Rg	95
Tested IES Rcs,h1	-12 %
Tested Duv	0.0001

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	40.92 W
Tested Total Harmonic Distortion	10.94 %
Tested Power Factor	0.9785

VERSION HISTORY VIEW DETAILS

2024-02-13	Listed	5.1	Standard
2021-05-14	Listed	5.1	Standard