# **DesignLights Consortium**





Model Number	PLTM1B22121
Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	155 W
Reported Light Output	23250 lm
Reported CCT	4000 K
Reported CRI (Ra)	83
Product ID	S-NS9HRM
DLC Family Code	BCBAKQ
Listing Status	Listed
Date Qualified	2024-09-10

## **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting	
Technical Requirements Version	5.1	
Product ID	S-NS9HRM	
Manufacturer	Precision Lighting & Transformer, Inc	
Brand	PLT	
Model Number	PLTM1B22121	
Parent	Yes	
Classification	Premium	
DLC Family Code	BCBAKQ	
Input Power Type	AC	

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation High-Bay Luminaires for Commercial and Industrial Buildings		

## **CONTROL FEATURES VIEW DETAILS**

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	23250 lm
Reported Efficacy (AC)	150 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83
Reported R9	6
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Minimum Light Output	17940 lm
Reported Maximum Light Output	23405 lm
Reported Minimum CCT	4000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	23250 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	155 W
Reported Total Harmonic Distortion	8.7 %
Reported Power Factor	0.963
Reported Minimum Input Wattage	115 W
Reported Maximum Input Wattage	155
Reported Default Input Wattage	155 W
Voltage Range	120-277 V

## **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Voltage for Minimum Efficacy	120	
-------------------------------------	-----	--

Tested Light Output	22440 lm
Tested Efficacy (AC)	150.74 lm/W
Tested CCT	3810 K
Tested CRI (Ra)	83
Tested R9	6
Tested IES Rf	84
Tested IES Rg	95
Tested IES Rcs,h1	-12 %
Tested Duv	-0.00109

## **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Input Wattage	148.9 W
Tested Total Harmonic Distortion	10.6 %
Tested Power Factor	0.943

## **VERSION HISTORY VIEW DETAILS**

2024-09-10	Listed	5.1	Premium