DesignLights Consortium





Model Number	PLTM1B33121	
Classification	Premium	
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings	
Reported Input Wattage	230 W	
Reported Light Output	34500 lm	
Reported CCT	4000 K	
Reported CRI (Ra)	83	
Product ID	S-PW8F2X	
DLC Family Code	BCBAKR	
Listing Status	Listed	
Date Qualified	2024-09-10	

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-PW8F2X
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM1B33121
Parent	Yes
Classification	Premium
DLC Family Code	BCBAKR
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation High-Bay Luminaires for Commercial and Industrial Buildings		

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	34500 lm
Reported Efficacy (AC)	150 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83
Reported R9	9
Reported IES Rf	83
Reported IES Rg	94
Reported IES Rcs,h1	-12
Reported Minimum Light Output	28860 lm
Reported Maximum Light Output	34500 lm
Reported Minimum CCT	4000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	34500 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	230 W
Reported Total Harmonic Distortion	5 %
Reported Power Factor	0.959
Reported Minimum Input Wattage	185 W
Reported Maximum Input Wattage	230
Reported Default Input Wattage	230 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|--|

Tested Light Output	33425 lm
Tested Efficacy (AC)	150.52 lm/W
Tested CCT	3975 K
Tested CRI (Ra)	83
Tested R9	9
Tested IES Rf	83
Tested IES Rg	94
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0013

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	222.1 W
Tested Total Harmonic Distortion	5 %
Tested Power Factor	0.959

VERSION HISTORY VIEW DETAILS

2024-09-10	Listed	5.1	Premium