

4" LED FIRE RATED RECESSED DOWNLIGHT







providing a reinforced and heat resistant steel casing

- Selectable color temperature: 27K, 3K, 35K, 4K & 5K
- Junction box with commercial grade driver included
- Triac Dimmable, Certififed airtight, IC rated
- Easy installation NO ADDITIONAL BOX REQUIRED





















DIMENSION



INSTALLATION

Cut Hole Size Ø4-1/4"(108mm)



SPECIFICATIONS			
Model	PLT-12993		
Watts	12W		
Light Ouput(Im)	883lm***		
Size	4in		
Default Driver Input	AC120V,60HZ		
Color Temperature(K)	5-color field selectable CCT - 2700K, 3000K, 3500K, 4000K, 5000K		
CRI	90Ra (80Ra Optional*)		
Dimming	Triac Dimming		
Power Factor	>0.9		
Approved Location	Wet Location		
Air Tight	Yes		
Operating Temp.	(-4°F~104°F) -20~40°C		
Beam Angle	120°		

PACKAGE	
Weight.(g)	332g
Qty/CTN (pcs)	18pcs/CTN
Box Dimension	L440*W285*H220mm
Gross Weight	7.58kg/CTN

- *80 CRI version NPS-00147 Special Order item, call 1-800-624-4488.
- **Special Order items. Call 1-800-624-4488.

Accessories

Extension Cables NPS-00116** 4ft flexible connector



NPS-00117** 6ft flexible connector, for use with Gimbal/s

for use with Gimbal/s

lim LED fixtures

lim LED fixtures





NPS-00118**

10ft flexible connector, for use with Gimbal/ slim LED fixtures

NPS-00119**

20ft flexible connector. for use with Gimbal/ slim LED fixtures



Goof Ring



PLT-12713 4" Goof Ring Inside Diameter - 4 3/16" (106.8mm) Outside Diameter - 5 3/4" (146mm)

Thickness - 1mm for use with Gimbal/ slim LED fixtures

Mounting Plate





4" new construction pre-mounting plate Opening Ø4 1/4"(108mm)



NPS-00123**

4" new construction pre-mounting plate with collar for use with screw down "C" style Opening Ø4 3/8"(110mm)



PLT-12987

3"/4"/6" new construction pre-mounting plate opening Ø3"(75mm), Ø4-3/8"(110mm), Ø6-1/4"(160mm)

^{***}See Selectable Table on page 2 for full breakdown.

SELECTABLE TABLE

Wattage	CCT	Lumens	LPW
12W	2700K	785	65
	3000K	844	70
	3500K	883	74
	4000K	881	73
	5000K	856	71