



## DESCRIPTION

Replace existing fluorescent wraparound fixture with these LED wraparound fixtures to reduce maintenance and energy costs.

## FEATURES

- Efficiently replaces a 4-lamp fluorescent fixture
- Delivers up to 117 LPW; output will vary depending on the wattage selected
- Wide body helps cover any marks or imperfections left by old fixtures
- 0-10V dimming

## LISTINGS

- UL rated for damp locations
- RoHS
- DesignLights Consortium® 5.1 Standard - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance; DLC PN: PLTM947132

## PERFORMANCE

- CRI: 80+
- CCT: 5000K
- LED L70 Life Hours: 100,000

## THERMAL

- -4°F to 122°F (-20°C to 50°C) operating temperature

## ELECTRICAL

- THD: <20%
- Power Factor: >0.9
- Input Voltage: 120-277V
- Dimmable power supply (0-10V)

## INSTALLATION

- Designed for surface mounting with included mounting hardware; see installation instructions for more details

## CONSTRUCTION

- Steel plate housing with white finish and plastic endcap
- PMMA lens protects LEDs while evenly distributing light

## WARRANTY

- 5-year limited warranty; see [pltsolutions.com](http://pltsolutions.com) for warranty details

<b>Project name</b>	<b>Type</b>
<b>Catalog number</b>	
<b>Comments</b>	<b>Voltage</b>
<b>Approved by</b>	<b>Date</b>



## APPLICATIONS

- Stairways
- Bathrooms
- Utility and Storage Areas
- Hallways
- Offices

## PERFORMANCE SUMMARY

Item #	Watts	Lumens	LPW	CCT	CRI	Dimming	Voltage	Replaces	DLC #	DLC Level
PLT-80047	65W	7605	117	5000K	80+	Yes	120-277V	4 Lamp Fluorescent	PLTM947132	5.1 Standard

## DIMENSIONS

### **DIMENSIONS:**

Length: 47.6"

Height: 3"

Width: 10"

Weight: 7.05 lbs.

