DesignLights Consortium





Model Number	ESXF4 ALO SWW2 YS DDB
Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	150 W
Reported Light Output	19583 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-K7SWB8
DLC Family Code	PPPTSA
Listing Status	Listed
Date Qualified	2022-06-06

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-K7SWB8
Manufacturer	Acuity Brands Lighting
Brand	Lithonia Lighting
Model Number	ESXF4 ALO SWW2 YS DDB
Parent	No
Classification	Premium
DLC Family Code	PPPTSA
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	High Output	
Primary Use Designation	Architectural Flood and Spot Luminaires	

CONTROL FEATURES VIEW DETAILS

Yes
Continuous Dimming to 10% or below
No
Exterior Photocell
0-10V Analog
No
Yes
Yes
No
Yes
Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

19583 lm
131 lm/W
3000 K
80
20
85
97
-10
15508 lm
20819 lm
3000 K
5000 K
20819 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	111 W
Reported Maximum Input Wattage	150
Reported Default Input Wattage	150 W

Voltage Range	120-277 V
voltage range	120-211 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Straight Down
---------------------------------------------	---------------

VERSION HISTORY VIEW DETAILS

22-06-06	Listed	5.1	Premium	
----------	--------	-----	---------	--