

DesignLights Consortium



Model Number	CPANL 2X4 ALO6 SWW7 Mx
Classification	Standard
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	53.899 W
Reported Light Output	6591.81 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	P3ZBXPS0
DLC Family Code	PPPTPO
Listing Status	Listed
Date Qualified	2021-04-26

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	P3ZBXPS0
Manufacturer	Acuity Brands Lighting
Brand	LITHONIA
Model Number	CPANL 2X4 ALO6 SWW7 Mx
Parent	Yes
Classification	Standard
DLC Family Code	PPPTPO
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Troffer
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	6591.81 lm
Reported Efficacy (AC)	122.29 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	6
Reported IES Rf	85
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Minimum Light Output	4359 lm
Reported Maximum Light Output	6580 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5000 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	53.899 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	34.4 W
Reported Maximum Input Wattage	55.1
Reported Default Input Wattage	42 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	277
Tested Light Output	6591.81 lm
Tested Efficacy (AC)	122.27 lm/W
Tested CCT	3473 K
Tested CRI (Ra)	83
Tested R9	6
Tested IES Rf	85
Tested IES Rg	96
Tested IES Rcs,h1	-12 %
Tested Duv	0.0024

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	53.91 W
Tested Total Harmonic Distortion	11.77 %
Tested Power Factor	0.9775

VERSION HISTORY VIEW DETAILS

2021-05-14	Listed	5.1	Standard
------------	--------	-----	----------