DesignLights Consortium





| Model Number | PLTMA4131412 |
|------------------------|----------------------------------|
| Classification | Standard |
| Primary Use | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 35 W |
| Reported Light Output | 4060 lm |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 84 |
| Product ID | S-3N36W7 |
| DLC Family Code | EMWBCL |
| Listing Status | Listed |
| Date Qualified | 2024-09-30 |
| | |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-3N36W7 |
| Manufacturer | Precision Lighting & Transformer, Inc |
| Brand | PLT |
| Model Number | PLTMA4131412 |
| Parent | Yes |
| Classification | Standard |
| DLC Family Code | EMWBCL |
| Length | 4.0 ft |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires |
|--|-------------------|
| General Application | Linear Ambient |
| Primary Use Designation Direct Linear Ambient Luminaires | |

CONTROL FEATURES VIEW DETAILS

10/7/24, 12:33 PM

| Integral Controls | No |
|--|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No |
| Sensor Type | No |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No |
| Field Adjustable Light Output | Yes |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 4060 lm |
|-------------------------------|----------|
| Reported Efficacy (AC) | 116 lm/W |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 84 |
| Reported R9 | 11 |
| Reported IES Rf | 84 |
| Reported IES Rg | 92 |
| Reported IES Rcs,h1 | -12 |
| Reported Minimum Light Output | 4060 lm |
| Reported Maximum Light Output | 4060 lm |
| Reported Minimum CCT | 3500 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 4060 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 35 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 8.8 % |
| Reported Power Factor | 0.971 |
| Reported Minimum Input Wattage | 35 W |
| Reported Maximum Input Wattage | 35 |
| Reported Default Input Wattage | 35 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

120

Tested Voltage for Minimum Efficacy

10/7/24, 12:33 PM

| Tested Light Output | 4019 lm |
|----------------------|-------------|
| Tested Efficacy (AC) | 116.01 lm/W |
| Tested CCT | 3477 K |
| Tested CRI (Ra) | 84 |
| Tested R9 | 11 |
| Tested IES Rf | 84 |
| Tested IES Rg | 92 |
| Tested IES Rcs,h1 | -12 % |
| Tested Duv | -0.0001 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Input Wattage | 34.6 W |
|----------------------------------|--------|
| Tested Total Harmonic Distortion | 9.5 % |
| Tested Power Factor | 0.971 |

VERSION HISTORY VIEW DETAILS

| 2024-09-30 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
|------------|--------|-----|----------|