# **DesignLights Consortium**





| Model Number           | PLTMA8332412                     |
|------------------------|----------------------------------|
| Classification         | Standard                         |
| Primary Use            | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 65 W                             |
| Reported Light Output  | 7800 lm                          |
| Reported CCT           | 3500 K                           |
| Reported CRI (Ra)      | 83                               |
| Product ID             | S-8BVHNX                         |
| DLC Family Code        | <u>EMWBCM</u>                    |
| Listing Status         | Listed                           |
| Date Qualified         | 2024-09-30                       |

### PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List         | Solid State Lighting                  |
|--------------------------------|---------------------------------------|
| Technical Requirements Version | 5.1                                   |
| Product ID                     | S-8BVHNX                              |
| Manufacturer                   | Precision Lighting & Transformer, Inc |
| Brand                          | PLT                                   |
| Model Number                   | PLTMA8332412                          |
| Parent                         | Yes                                   |
| Classification                 | Standard                              |
| DLC Family Code                | EMWBCM                                |
| Length                         | 8.0 ft                                |
| Input Power Type               | AC                                    |

### PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Luminaires                |
|-------------------------|----------------------------------|
| General Application     | Linear Ambient                   |
| Primary Use Designation | Direct Linear Ambient Luminaires |

# **CONTROL FEATURES VIEW DETAILS**

| Integral Controls                      | No                                 |
|--|------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No                                 |
| Sensor Type                            | No                                 |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No                                 |
| Field Adjustable Light Output          | No                                 |
| White-Tunable                          | Yes                                |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 7800 lm  |
|-------------------------------|----------|
| Reported Efficacy (AC)        | 120 lm/W |
| Reported CCT                  | 3500 K   |
| Reported CRI (Ra)             | 83       |
| Reported R9                   | 11       |
| Reported IES Rf               | 84       |
| Reported IES Rg               | 96       |
| Reported IES Rcs,h1           | -12      |
| Reported Minimum Light Output | 7800 lm  |
| Reported Maximum Light Output | 8060 lm  |
| Reported Minimum CCT          | 3500 K   |
| Reported Maximum CCT          | 5000 K   |
| Reported Default Light Output | 7800 lm  |

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 65 W      |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 9.1 %     |
| Reported Power Factor              | 0.979     |
| Reported Minimum Input Wattage     | 65 W      |
| Reported Maximum Input Wattage     | 65        |
| Reported Default Input Wattage     | 65 W      |
| Voltage Range                      | 120-277 V |

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Tested Voltage for Minimum Efficacy | 120 |
|-------------------------------------|-----|
|                                     |     |

| Tested Light Output  | 7136 lm    |
|----------------------|------------|
| Tested Efficacy (AC) | 119.7 lm/W |
| Tested CCT           | 3423 K     |
| Tested CRI (Ra)      | 83         |
| Tested R9            | 11         |
| Tested IES Rf        | 84         |
| Tested IES Rg        | 96         |
| Tested IES Rcs,h1    | -12 %      |
| Tested Duv           | 0.0002     |

# **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Tested Input Wattage             | 59.6 W |
|----------------------------------|--------|
| Tested Total Harmonic Distortion | 9.1 %  |
| Tested Power Factor              | 0.979  |

# **VERSION HISTORY VIEW DETAILS**

| 024-09-30 Lis | isted | 5.1 | Standard |
|---------------|-------|-----|----------|
|---------------|-------|-----|----------|