

DesignLights Consortium



Model Number	ET8-4040T-15
Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	15 W
Reported Light Output	2200 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	S-11KXLC
DLC Family Code	CCCINB
Listing Status	Listed
Date Qualified	2024-06-11

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-11KXLC
Manufacturer	Euri Lighting
Brand	Euri Lighting
Model Number	ET8-4040T-15
Parent	No
Classification	Standard
DLC Family Code	CCCINB
Length	4.0 ft
Input Power Type	AC
Notes	Dimmable via an external accessory

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T8 Four-Foot
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	Input signal from external control source
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	229 °
Reported Light Output	2200 lm
Reported Efficacy (AC)	146.7 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	5
Reported IES Rf	83
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Default Light Output	2200 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	15 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	15 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2024-06-11	Listed	5.1	Standard
------------	--------	-----	----------