

Fluorescent T8 Tube: GLASS

PLT-13607

DESCRIPTION

Featuring triple-wound tungsten and a Krypton/argon gas mixture, these F32T8/835 fluorescent T8 tubes are designed to outperform other similar lamps.

FEATURES

- F32T8/835
- · Frosted glass lens reduces visual glare
- Krypton/argon gas mixture reduces energy consumption
- Triple-wound tungsten improves electrode emissions
- · Phosphor coating keeps colors consistent
- · Metal caps and brass pins provide better contact

LISTINGS

- TCLP
- EISA
- RoHS

WARRANTY

· 2-year limited warranty; see pltsolutions.com for warranty details

Project name	Туре
Catalog number	
Comments	Voltage
Approved by	Date





APPLICATIONS

- Office Lighting
- · High Bays
- Industrial Strips
- Warehouses
- Stairwells

	Power Consumption	32 Watt			
	Initial Lumens	3100			
	Means Lumens	2950			
PERFORMANCE	Efficacy (LPW)	97			
	CRI	85			
	сст	3500K			
	Life Hours	24,000			
	Operating Temperature	-4°F to 113°F or (-20°C to 45°C)			
CONSTRUCTION	Base	Medium Bi-Pin			
	Lens	Frosted			
	Certifications	TCLP, EISA			
LISTINGS	Material Usage	RoHS - No mercury or lead			
	Environment	Suitable for use in enclosed fixtures - Damp Location Rated			

PERFORMANCE SUMMARY										
Item #	Order Code	Watts	Initial Lumens	Mean Lumens	LPW	сст	CRI	Envelope	Life Hours	Length
PLT-13607	F32T8/835	32	3100	2950	97	3500K	85	Glass	24,000	4'

DIMENSIONS



DIMENSIONS:

Length – 47.2" Diameter – 1"