DesignLights Consortium





| Model Number | PLTSU43211 |
|------------------------|----------------------------------|
| Classification | Standard |
| Primary Use | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 35 W |
| Reported Light Output | 4025 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 81 |
| Product ID | S-ZKR3PB |
| DLC Family Code | EMWBZO |
| Listing Status | Listed |
| Date Qualified | 2024-12-13 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|---------------------------------------|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | S-ZKR3PB | | |
| Manufacturer | Precision Lighting & Transformer, Inc | | |
| Brand | PLT | | |
| Model Number | PLTSU43211 | | |
| Parent | Yes | | |
| Classification | Standard | | |
| DLC Family Code | EMWBZO | | |
| Length | 3.0 ft | | |
| Input Power Type | AC | | |
| | | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires Linear Ambient | |
|-------------------------|----------------------------------|--|
| General Application | | |
| Primary Use Designation | Direct Linear Ambient Luminaires | |

CONTROL FEATURES VIEW DETAILS

1 of 3

| Integral Controls | No |
|--|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No |
| Sensor Type | No |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No |
| Field Adjustable Light Output | Yes |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 4025 lm |
|-------------------------------|----------|
| Reported Efficacy (AC) | 115 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 81 |
| Reported R9 | 2 |
| Reported IES Rf | 83 |
| Reported IES Rg | 97 |
| Reported IES Rcs,h1 | -12 |
| Reported Minimum Light Output | 2300 lm |
| Reported Maximum Light Output | 4025 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5700 K |
| Reported Default Light Output | 4025 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 35 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 20 W |
| Reported Maximum Input Wattage | 35 |
| Reported Default Input Wattage | 35 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

2 of 3 12/16/2024, 9:17 AM

| Tested Voltage for Minimum Efficacy | 120 |
|-------------------------------------|-------------|
| Tested Light Output | 4095 lm |
| Tested Efficacy (AC) | 114.83 lm/W |
| Tested CCT | 2951 K |
| Tested CRI (Ra) | 81 |
| Tested R9 | 2 |
| Tested IES Rf | 83 |
| Tested IES Rg | 97 |
| Tested IES Rcs,h1 | -12 % |
| Tested Duv | -0.0027 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Input Wattage | 35.7 W |
|----------------------------------|--------|
| Tested Total Harmonic Distortion | 5.7 % |
| Tested Power Factor | 0.945 |

VERSION HISTORY VIEW DETAILS

| 2024-12-13 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
| | | | |

3 of 3