# **DesignLights Consortium**





| Model Number           | PLTSU48411                       |
|------------------------|----------------------------------|
| Classification         | Standard                         |
| Primary Use            | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 100 W                            |
| Reported Light Output  | 11500 lm                         |
| Reported CCT           | 3000 K                           |
| Reported CRI (Ra)      | 81                               |
| Product ID             | S-7G4ZBY                         |
| DLC Family Code        | EMWBZO                           |
| Listing Status         | Listed                           |
| Date Qualified         | 2024-12-13                       |

# **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Product List         | Solid State Lighting                  |  |  |  |
|--------------------------------|---------------------------------------|--|--|--|
| Qualified Product List         | Solid State Lighting                  |  |  |  |
| Technical Requirements Version | 5.1                                   |  |  |  |
| Product ID                     | S-7G4ZBY                              |  |  |  |
| Manufacturer                   | Precision Lighting & Transformer, Inc |  |  |  |
| Brand                          | PLT                                   |  |  |  |
| Model Number                   | PLTSU48411                            |  |  |  |
| Parent                         | No                                    |  |  |  |
| Classification                 | Standard                              |  |  |  |
| DLC Family Code                | EMWBZO                                |  |  |  |
| Length                         | 8.0 ft                                |  |  |  |
| Input Power Type               | AC                                    |  |  |  |

# **PRODUCT CATEGORIZATION VIEW DETAILS**

| Category                | Indoor Luminaires                |  |
|-------------------------|----------------------------------|--|
| General Application     | Linear Ambient                   |  |
| Primary Use Designation | Direct Linear Ambient Luminaires |  |

# **CONTROL FEATURES VIEW DETAILS**

1 of 3

| Integral Controls                      | No                                 |
|--|------------------------------------|
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No                                 |
| Sensor Type                            | No                                 |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No                                 |
| Field Adjustable Light Output          | Yes                                |
| White-Tunable                          | Yes                                |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output         | 11500 lm |  |  |  |
|-------------------------------|----------|--|--|--|
| Reported Efficacy (AC)        | 115 lm/W |  |  |  |
| Reported CCT                  | 3000 K   |  |  |  |
| Reported CRI (Ra)             | 81       |  |  |  |
| Reported R9                   | 1        |  |  |  |
| Reported IES Rf               | 83       |  |  |  |
| Reported IES Rg               | 97       |  |  |  |
| Reported IES Rcs,h1           | -12      |  |  |  |
| Reported Minimum Light Output | 6900 lm  |  |  |  |
| Reported Maximum Light Output | 11500 lm |  |  |  |
| Reported Minimum CCT          | 3000 K   |  |  |  |
| Reported Maximum CCT          | 5700 K   |  |  |  |
| Reported Default Light Output | 11500 lm |  |  |  |

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage             | 100 W     |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 %      |
| Reported Power Factor              | 0.9       |
| Reported Minimum Input Wattage     | 60 W      |
| Reported Maximum Input Wattage     | 100       |
| Reported Default Input Wattage     | 100 W     |
| Voltage Range                      | 120-277 V |

# **VERSION HISTORY VIEW DETAILS**

2 of 3 12/16/2024, 9:53 AM

Firefox

| 2024-12-13 | Lietad | 5 1  | Standard |
|------------|--------|------|----------|
| 2024-12-13 | Listed | J. I | Otanuaru |

3 of 3