# **DesignLights Consortium**





Model Number	PLTSU22111
Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	30 W
Reported Light Output	3450 lm
Reported CCT	3000 K
Reported CRI (Ra)	83
Product ID	S-SZ10X4
DLC Family Code	EMWBZN
Listing Status	Listed
Date Qualified	2024-12-13

## **PRODUCT INFORMATION VIEW DETAILS**

Solid State Lighting
5.1
S-SZ10X4
Precision Lighting & Transformer, Inc
PLT
PLTSU22111
Yes
Standard
EMWBZN
2.0 ft
AC

## **PRODUCT CATEGORIZATION VIEW DETAILS**

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

## **CONTROL FEATURES VIEW DETAILS**

1 of 3

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3450 lm
Reported Efficacy (AC)	115 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	9
Reported IES Rf	85
Reported IES Rg	95
Reported IES Rcs,h1	-11
Reported Minimum Light Output	2300 lm
Reported Maximum Light Output	3450 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	4000 K
Reported Default Light Output	3450 lm

# REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	30 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	20 W
Reported Maximum Input Wattage	30
Reported Default Input Wattage	30 W
Voltage Range	120-277 V

# **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

2 of 3

Tested Voltage for Minimum Efficacy	120
Tested Light Output	3431 lm
Tested Efficacy (AC)	114.3 lm/W
Tested CCT	2978 K
Tested CRI (Ra)	83
Tested R9	9
Tested IES Rf	85
Tested IES Rg	95
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0017

#### **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Input Wattage	30 W
Tested Total Harmonic Distortion	6.2 %
Tested Power Factor	0.946

# **VERSION HISTORY VIEW DETAILS**

2024-12-13	Listed	5.1	Standard

3 of 3