

# DesignLights Consortium



|                        |                                  |
|------------------------|----------------------------------|
| Model Number           | PLTSU23211                       |
| Classification         | Standard                         |
| Primary Use            | Direct Linear Ambient Luminaires |
| Reported Input Wattage | 40 W                             |
| Reported Light Output  | 4600 lm                          |
| Reported CCT           | 3000 K                           |
| Reported CRI (Ra)      | 83                               |
| Product ID             | S-BWYV25                         |
| DLC Family Code        | <a href="#">EMWBZN</a>           |
| Listing Status         | Listed                           |
| Date Qualified         | 2024-12-13                       |

## PRODUCT INFORMATION VIEW DETAILS

|                                |                                       |
|--------------------------------|---------------------------------------|
| Qualified Product List         | Solid State Lighting                  |
| Technical Requirements Version | 5.1                                   |
| Product ID                     | S-BWYV25                              |
| Manufacturer                   | Precision Lighting & Transformer, Inc |
| Brand                          | PLT                                   |
| Model Number                   | PLTSU23211                            |
| Parent                         | No                                    |
| Classification                 | Standard                              |
| DLC Family Code                | EMWBZN                                |
| Length                         | 3.0 ft                                |
| Input Power Type               | AC                                    |

## PRODUCT CATEGORIZATION VIEW DETAILS

|                         |                                  |
|-------------------------|----------------------------------|
| Category                | Indoor Luminaires                |
| General Application     | Linear Ambient                   |
| Primary Use Designation | Direct Linear Ambient Luminaires |

## CONTROL FEATURES VIEW DETAILS

|  |                                    |
|--|------------------------------------|
| Integral Controls                      | No                                 |
| Dimming Capability and Range           | Continuous Dimming to 10% or below |
| Integral Control Capability            | No                                 |
| Sensor Type                            | No                                 |
| SSL V5 Wired Communication Protocol    | 0-10V Analog                       |
| SSL V5 Wireless Communication Protocol | No                                 |
| Field Adjustable Light Output          | Yes                                |
| White-Tunable                          | Yes                                |
| Warm-Dimming                           | No                                 |
| Field Adjustable Light Distribution    | No                                 |

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|                               |          |
|-------------------------------|----------|
| Reported Light Output         | 4600 lm  |
| Reported Efficacy (AC)        | 115 lm/W |
| Reported CCT                  | 3000 K   |
| Reported CRI (Ra)             | 83       |
| Reported R9                   | 8        |
| Reported IES Rf               | 85       |
| Reported IES Rg               | 95       |
| Reported IES Rcs,h1           | -11      |
| Reported Minimum Light Output | 2300 lm  |
| Reported Maximum Light Output | 4600 lm  |
| Reported Minimum CCT          | 3000 K   |
| Reported Maximum CCT          | 4000 K   |
| Reported Default Light Output | 4600 lm  |

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

|                                    |           |
|------------------------------------|-----------|
| Reported Input Wattage             | 40 W      |
| Reported Total Harmonic Distortion | 20 %      |
| Reported Power Factor              | 0.9       |
| Reported Minimum Input Wattage     | 20 W      |
| Reported Maximum Input Wattage     | 40        |
| Reported Default Input Wattage     | 40 W      |
| Voltage Range                      | 120-277 V |

## VERSION HISTORY VIEW DETAILS

---

|            |        |     |          |
|------------|--------|-----|----------|
| 2024-12-13 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|