



Sabre Wattage and Color Selectable LED Area Lights

DESCRIPTION

Outlasting and outperforming traditional metal halide fixtures, these beam angle, wattage, and color selectable LED area lights are ideal for a variety of outdoor applications.

FEATURES

- Up to 1160 LPW ultra-high efficiency delivers superior performance over older HID fixtures
- Output varies depending on the wattage and color temperature selected, see Selectable Table for full breakdown
- Switchable lenses allow you to swap between Type III (pre-installed) and Type V light distribution
- Type III light distribution projects light outwards with a lateral width of 40 degrees
- Type V light distribution projects light in a circular pattern with the same intensity at all angles
- 0-10V dimming
- Mounting accessories sold separately, see Mounting Accessories sections for full list of compatible mounts
- Shielding accessories sold separately, see Shields sections for full list of compatible mounts
- Wattage and color temperature can be adjusted using the switched location on the driver of the fixture; see installation instructions for more information

LISTINGS

- UL Listed for wet locations
- IP65
- IK08

PERFORMANCE

- CRI: >80
- CCT: 3000K, 4000K, & 5000K
- LED L70 Life Hours: 155,000 hours (PLT-13144), 145,000 hours (PLT-13145)
- Light Distribution: Type V
- Philips Lumiled LEDs & Sosen driver

THERMAL

- -40°F to 122°F (-40°C to 50°C) operating temperature

ELECTRICAL

- THD: ≤20%
- Power Factor: ≥0.9
- Input Voltage: 120-277V
- Dimmable power supply (0-10V)
- Surge Protection: 6kV, 10kV

INSTALLATION

- Designed to be mounted with Series Series slipfitters, straight arms, or U brackets (all sold separately), see Mounting Accessories section for full list of compatible products. See installation instructions for more information on how to install these fixtures.

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



CONSTRUCTION

- Low profile die-cast aluminum housing
- Durable dark bronze powder coat finish
- Polycarbonate lens

WARRANTY

- 5-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Parking Lots
- Automotive Dealerships
- Roadways
- Campuses
- Area Security Lighting
- Airports

PERFORMANCE SUMMARY

Item #	Family	Watts*	CCT*	CRI	Dimming	Voltage	Replaces	Light Distribution	BUG
PLT-13144	Sabre Series	100/ 120/ 150	3000K/ 4000K/ 5000K	>80	0-10V	120-277V	MH400	Type III & Type V	B4-U0-G4
PLT-13145	Sabre Series	260/ 280/ 300	3000K/ 4000K/ 5000K	>80	0-10V	120-277V	MH1000	Type III & Type V	B5-U0-G5

* See Selectable Table for full breakdown

SELECTABLE TABLE

SKU	Wattage	Voltage	CCT	Lumens	Efficacy
PLT-13144	100	AC120V	3000K	14,707	147
			4000K	15,193	152
			5000K	15,276	153
	120		3000K	16,833	140
			4000K	17,666	147
			5000K	17,617	147
	150		3000K	21,782	145
			4000K	21,507	143
			5000K	22,238	148
PLT-13145	200	AC120V	3000K	30,734	154
			4000K	31,924	160
			5000K	31,972	160
	240		3000K	35,616	148
			4000K	37,228	155
			5000K	37,099	155
	300		3000K	43,363	145
			4000K	45,922	153
			5000K	45,605	152

MOUNTING ACCESSORIES (SOLD SEPARATLY)

Item #	Family	Description	Adjustable	Compatible Fixtures
PLT-13146	Sabre Series	Slipfitter Mount – for 2 ½ in. Tenon - Bronze	0-90°	PLT-13144, PLT-13145
PLT-13147	Sabre Series	6 in. Aluminum Adjustable Arm – for Square Poles - Bronze	0-35°	PLT-13144, PLT-13145
PLT-13148	Sabre Series	Adjustable U-Bracket – Bronze – for 150W PLT Sabre Series LED Area Lights	0-180°	PLT-13144
PLT-13149	Sabre Series	Adjustable U-Bracket – Bronze – for 300W PLT Sabre Series LED Area Lights	0-180°	PLT-13145

SHIELDS

Item #	Family	Description	Compatible Fixture
PLT-13153	Sabre Series	Front Cutoff Shield	PLT-13144
PLT-13154	Sabre Series	Back Cutoff Shield	
PLT-13155	Sabre Series	Left Cutoff Shield	
PLT-13156	Sabre Series	Right Cutoff Shield	
PLT-13157	Sabre Series	Front Cutoff Shield	PLT-13145
PLT-13158	Sabre Series	Back Cutoff Shield	
PLT-13159	Sabre Series	Left Cutoff Shield	
PLT-13160	Sabre Series	Right Cutoff Shield	

FIXTURES DIMENSIONS

PLT-13144

Length: 19.5"
 Height: 3.1"
 Width: 10.6"
 Weight: 9.01 lbs



PLT-13145


Length: 21.5"
 Height: 3.1"
 Width: 12.7"
 Weight: 11.22 lbs



MOUNTS DIMENSIONS


PLT-13146:

Length - 6.95"
 Height - 4.88"
 Width - 2.84"
 Diameter - 2.44"
 Weight - 1.44 lbs




PLT-13147:

Length - 9"
 Height - 6.28"
 Width - 4.88"
 Weight - 2.21 lbs




PLT-13148:

Length - 11.82"
 Height - 2.05"
 Width - 8.55"
 Weight - 1.35 lbs



PLT-13149:

Length - 13.86"
 Height - 2.05"
 Width - 8.55"
 Weight - 1.99 lbs



SHEILDS DIMENSIONS

PLT-13153:

Length – 10.75"

Width – 5.95"

Height – 2.95"

Wight – 1.25 lbs

PLT-13154:

Length – 10.75"

Width – 5.95"

Height – 2.95"

Wight – 1.25 lbs

PLT-13155:

Length – 10.24"

Width – 5.56"

Height – 0.48"

Wight – 1.02 lbs

PLT-13156:

Length – 10.24"

Width – 5.56"

Height – 0.48"

Wight – 1.02 lbs

PLT-13157:

Length – 12.80"

Width – 6.74"

Height – 6.78"

Wight – 1.27 lbs

PLT-13158:

Length – 12.80"

Width – 6.74"

Height – 6.78"

Wight – 1.27 lbs

PLT-13159:

Length – 12.21"

Width – 6.78"

Height – 0.48"

Wight – 1.3 lbs

PLT-13160:

Length – 12.21"

Width – 6.78"

Height – 0.48"

Wight – 1.3 lbs