plano (A) RCH **LFLD** | Everest **LED Flood Light Luminaire** The Ideal Flood Light Easily Accessible Multi-Function Operations Control Center Built-In OCC OPERATIONS CO **ARCHIPELAGO**

Reliable. **Energy Efficient.**



DURABLE ALUMINUM SHELL

Rugged One-Piece Die-Cast Aluminum Body Housing with UV Resistant Powder Coat Finish Offers Outstanding Corrosion Protection.



OUTSTANDING BENEFITS

Featuring outstanding photometric performance, uniform illumination, low-profile design, high efficiency, long lifespan, and easy installation



WET LOCATION LISTED

Everest-Series flood light fixtures are specifically designed and sealed to withstand exposure to rain, snow, and other forms of moisture



5-Year Warranty



50,000 Hours



100

Lumileds LEDs provide bright, long-lasting light known for their energy efficiency and beautiful illumination



SELECTAD

KNUCKLE



YOKE TRUNNION MOUNTS AVAILABLE



SLIP FITTER

Dimming

Built-In Photocell

Suitable for use in -40°F to 113°F

WATTselect Options

Up to 150W

CCTselect Options

3000K | 4000K | 5000K

Suitable for use in wet locations

Efficacy up to 140lm/W

Ordering Guide¹

Model Series	WATT	WATTselect (W)		CCTselect (K)	Series			Voltage	Finish			Photocell	
LFLD LED Flood Light	35 80 150	35W Max 80W Max 150W	-	3 3-CCTselect: 3000K 4000K 5000K	E1	Everest	-	U 120-277V	D B W #	Dark Bronze Black White Custom RAL#	/	PS Built-In Button Photocell	
CATALOG #:													
LFLD			-	3	E1		-	U			7	PS	

Options Guide²

□ KN Knuckle (35W/80W/150W) □ SP Slip-Fitter (80W/150W) Trunnion (150W) Yoke (35W/80W/150W) □ YK

- Only one selection may be applicable within the same category.
 Multiple selections may be applicable within the same option category. See Compatible Accessories below for details.
 Standard driver on-board SPD = 6KVa

Applications:























