DesignLights Consortium





| Model Number | EALH-150W1033cws |
|------------------------|--|
| Classification | Premium |
| Primary Use | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires |
| Reported Input Wattage | 148.3 W |
| Reported Light Output | 25677 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 73 |
| Product ID | S-CTHZ06 |
| DLC Family Code | WWWYHQ |
| Listing Status | Listed |
| Date Qualified | 2025-01-09 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-CTHZ06 |
| Manufacturer | Euri Lighting |
| Brand | EURI LIGHTING |
| Model Number | EALH-150W1033cws |
| Parent | Yes |
| Classification | Premium |
| DLC Family Code | WWWYHQ |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Outdoor Luminaires | |
|-------------------------|--|--|
| General Application | High Output | |
| Primary Use Designation | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | Yes | | |
|--|--|--|--|
| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
| Integral Control Capability | No | | |
| Sensor Type | Exterior Photocell, Sensor Receptacle, Occupancy Sensing | | |
| SSL V5 Wired Communication Protocol | 0-10V Analog | | |
| SSL V5 Wireless Communication Protocol | No | | |
| Field Adjustable Light Output | Yes | | |
| White-Tunable | Yes | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 25677 lm |
|-------------------------------|------------|
| Reported Efficacy (AC) | 173.2 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 73 |
| Reported R9 | -27 |
| Reported IES Rf | 74 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -16 |
| Reported Minimum Light Output | 17320 lm |
| Reported Maximum Light Output | 25677 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 25677 lm |
| Reported BUG Rating | B4 U3 G4 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 148.3 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 6.8 % |
| Reported Power Factor | 0.954 |
| Reported Minimum Input Wattage | 100 W |
| Reported Maximum Input Wattage | 148.3 |
| Reported Default Input Wattage | 148.3 W |
| Voltage Range | 277-480 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Tested Voltage for Minimum Efficacy | 277 |
|-------------------------------------|------------|
| Tested Light Output | 25677 lm |
| Tested Efficacy (AC) | 173.2 lm/W |
| Tested CCT | 2976 K |
| Tested CRI (Ra) | 73 |
| Tested R9 | -27 |
| Tested IES Rf | 74 |
| Tested IES Rg | 96 |
| Tested IES Rcs,h1 | -16 % |
| Tested Duv | -0.00196 |
| Tested BUG Rating | B4 U3 G4 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Input Wattage | 148.25 W |
|----------------------------------|----------|
| Tested Total Harmonic Distortion | 6.8 % |
| Tested Power Factor | 0.954 |

VERSION HISTORY VIEW DETAILS

| 2025-01-09 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
| | | | |