



DESCRIPTION

- Cost-effective LED ready vapor tight fixture
- Perfect for loading docks, stairwells, and utility lighting
- Utilizes 4 double-ended direct wire LED T8 tubes (sold separately) or Type C LED T8 tubes (sold separately), allowing for the light output and color temperature to be customized as needed

LISTINGS

- UL rated for wet locations
- IP65

ELECTRICAL

- Input Voltage: 120-277V
- Pre-wired non-shunted sockets

INSTALLATION

- Designed for surface mounting (mounting hardware included) or suspended mounting with included v-hooks (chain sold separately); see installation instructions for more information

CONSTRUCTION

- Heavy duty PC housing with gray finish and stainless-steel latches
- Frosted polycarbonate lens protects LEDs while evenly distributing light

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



WARRANTY

- 3-year limited warranty; see pltsolutions.com for warranty details

APPLICATIONS

- Utility Lighting
- Stairwell Lighting
- Parking Garages
- Hallways

ELECTRICAL	Lamp Type (Not Included)	T8 Double-Ended Direct Wire LED Lamps or T8 Type C LED Lamps
	Number of Lamps	4
	Input Voltage	120 - 277
CONSTRUCTION	Housing	Heavy duty PC
	Base Power Supply	Hard wired for Double-Ended Direct Wire T8 LED Lamps or Type C T8 LED Lamps
	Finish	Grey
LISTINGS	Certifications	UL Listed; IP65
	Environment	Suitable for Wet Locations

PERFORMANCE SUMMARY

Item#	# of Lamps	Length	Width	Height	Voltage	Warranty	Compatible Lamps
PLT-13632	4	98.8"	5.1"	3.3"	120-277V	3 Years	Double-Ended Direct Wire T8 LED Lamps/ Type C T8 LED Lamps

DIMENSIONS



DIMENSIONS

Length: 98.8"
Height: 3.3"
Width: 5.1"