

# Patio Light Stringers w/ Shades & LED Bulbs

Easily add lights to backyards, patios, and more with these patio light stringers sets. Each set includes bulbs and shades.

### **FEATURES**

- 10 suspended sockets spaced 12-inches apart
- · Can connect up to 96 sets end-to-end
- Weather-resistant SJTW wire withstands water and abrasion, making it ideal for permanent outdoor use
- Sockets feature water-resistant gaskets that seal around the bulbs, protecting against water entry
- · Standard household medium (E26) base
- · Molded male & female plugs without fuses
- · Sockets come with eyelets for running guywires
- 10 shatter-resistant LED S14 vintage bulbs included
- Comes with 10 shades to snap onto the socket; see Shades section for more information

### **LISTINGS**

- · ETL Listed for wet locations
- IP64

### **ELECTRICAL**

• Bulb Type: LED S14 Filament

Bulb Wattage: 1WBulb Finish: Amber

Stringer Max. Current: 8A
Stringer Max. Wattage: 250W
Socket Max. Wattage: 25W
Socket Type: Medium E26

Plug Type: 2-prong

#### CONSTRUCTION

- · Black or white 18AWG SJTW wire
- 10 sockets with gasketed seals
- 2-prong male plug; string terminates with female plug
- Shades made from iron, PVC rattan (PLT-13603 only), or natural fibers (PLT-13604 only)

Project name	Туре		
Catalog number			
Comments	Voltage		
Approved by	Date		















#### WARRANTY

 2-year limited warranty; see pltsolutions.com for warranty details

## **APPLICATIONS**

- Decks
- Patios
- Gazebos
- Backyards

# **PERFORMANCE SUMMARY**

Item #	# of Sockets	Socket Spacing	Socket Type	Wire Gauge	Wire Type	Lead Length	Tail Length	Plugs	Max. Wattage	Color	Shade Type*	Total Length
PLT-13599	10	12in	E26	18AWG	SJTW	4'	2'	Male/ Female	250W	Black	Black Hammered	15'
PLT-13600	10	12in	E26	18AWG	SJTW	4'	2'	Male/ Female	250W	White	White Ridged	15'
PLT-13601	10	12in	E26	18AWG	SJTW	4'	2'	Male/ Female	250W	Black	Black Galvanized	15'
PLT-13602	10	12in	E26	18AWG	SJTW	4'	2'	Male/ Female	250W	Black	Curved	15'
PLT-13603	10	12in	E26	18AWG	WTLS	4'	2'	Male/ Female	250W	Black	Hawaii	15'
PLT-13604	10	12in	E26	18AWG	SJTW	4'	2'	Male/ Female	250W	Black	Tahiti	15'

<sup>\*</sup>Shade must be fully snapped into place in order for the bulb to fully connect into the socket. Once shade is installed, it cannot be easily removed.

# **BULBS**

Shape	LED S14 Filament
Wattage	1W
Kelvin	2200K
Lumens	60
LPW	60
CRI	>75
Voltage	120V
Dimmable	No
Wattage Equivalent	11W Incan.
Bulb Finish	Amber
Filament Type	Straight
# of Filaments	1
Life Hours	15000
Listings	ETL Wet Location

# **SHADES**

SKU	Shade Type*	<b>Description Diameter</b>		Height
PLT-13599	Black Hammered	Iron hammered shade w/ black outer finish and white inner finish	8.07"	1.77"
PLT-13600	White Ridged	d Iron ridged shade w/ white outer and inner finish		1.57"
PLT-13601	Black Galvanized	lack Galvanized Iron shade w/ black outer finish and white reflector 7.28"		1.77"
PLT-13602	Curved	Iron curved shade w/ black outer finish and copper reflector	8.07"	2.17"
PLT-13603	Hawaii	Woven shade made of PVC rattan	11.81"	5.12"
PLT-13604	Tahiti	Woven shade made of natural straw-like fibers	11.81"	2.76"

<sup>\*</sup>Shade must be fully snapped into place for the bulb to fully connect into the socket. Once shade is installed, it cannot be easily removed.

### **DIMENSIONS**

# **STRINGER**

Total String Length - 15'

Lead Length - 4'

Tail Length - 2'

Bulb Spacing - 12"

Drop Length - 5.9"

# **LED S14 FILAMENT BULB**

Height - 3.27"

Diameter - 1.73"

# **BLACK HAMMERED SHADE**

Height - 1.77"

Diameter - 8.07"

# WHITE RIDGED SHADE

Height - 1.57"

Diameter - 7.87"

# **BLACK GALVANIZED SHADE**

Height - 1.77"

Diameter - 7.28"

### **CURVED SHADE**

Height - 2.17"

Diameter - 8.07"

# **HAWAII SHADE**

Height - 5.12"

Diameter - 11.81"

# **TAHITI SHADE**

Height - 2.76"

Diameter - 11.81"

# **WARNINGS**

- · Not for use with dimmers.
- Turn off the power before installing the shades and bulbs.
- Shade must be fully snapped into place in order for the bulb to fully connect into the socket. Once shade is installed, it cannot be easily removed.