

145 West Commercial Ave. Moonachie, NJ 07074 T: 800.528.5555

F: 800.441.7708 www.bulbrite.com



10.3W LED 5IN FLUSH MOUNT 5CCT WHITE DIMMABLE JA8 ltem #773603

Ordering Code LED10FLUSH/5/5CCT/927-950/J/WH/D UPC 739698736037

- Surface mounted 5" LED Flush Mount in white, black, and nickel
- Easy installation via mounting bracket to J-Box, included mounting bracket compatible with 5", 7" and 9" flush mount
- High light output, 5CCT Selectable (2700K/3000K/3500K/4000K/5000K
- Ideal for residential bedrooms, living rooms, bathrooms, laundry rooms, offices or family rooms









## **TECHNICAL SPECIFICATIONS**

Item # 773603	Watts 10.3	Bulb Type 5" FLUSH MOUN	Base 「E26	Volts 120	Finish/Description White	Beam Angle (°) 110	Color Temperature (CCT) 5 CCT - 27/30/35/40/50K
Color #N/A	CRI 90	Lumens 850	CBCP N/A	Average Hours 50000	M.O.L. (inches) 5	M.O.D. (inches) 0.73	Incandescent Equivalent 60
Energy Star N	DLC N	Title 24 Compliant	Safety Rated UL	Safety Rating Typ WET	eEnclosed Rated N	Dimmable Y	Warranty 5

Order Multiple QTY

10

## **APPLICATION SUGGESTIONS**







Commercial

Recessed

Direct Wire



## **Dimmer Compatibility Guide**

Product Family Name: Item Number: 773603

Ordering Code: LED10FLUSH/5/5CCT/927-950/J/WH/D

Item Number: Ordering Code:

	Manufacturer			Model Number	Overall Rating	Lamps per Dimmer		
			Product			Recommended	Maximum	Notes
						Minimum	Tested*	
			IllumaTech	IPI06	Good	1	6	Not smooth, Dead travel (HE 15%/LE 20%)
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton		SureSlide	6633-P	Bad	1	6	Flickers heavily w/5, not smooth w/6, Good with <5
			Vizia	VPI06-1LZ	Best	1	6	
			Toggler	TG-600	Good	1	6	Dims to <1%, SLIGHT flicker at MIN with <6
			Lumea	LGCL-600	Bad	1	6	80% at MAX with >2
	Lutron		Diva	DV-600	Good	1	6	Delay when ↑ from MIN, LE dead travel ~30%
			Skylark	S-600	Best	1	6	
			Maestro	MAW-600 CD703-PW	Bad Not Compatible	2	6	Not compatible with <2
	Legrand		Titan Harmony	D703-PTC	Bad	2	6	Not compatible with <2
			Harmony	H703-PTC	Bad	2	6	Not compatible with <2
			· · · · · · · · · · · · · · · · · · ·			2	_	
	Leviton		IllumaTech	IPL06	Good	1	6	HE dead travel (10%), significant delay when ↑ from MIN
			Sureslide	6674	Good	1	6	HE dead travel (30%)
			Decora	6672	Best	1	6	
			Decora Slide	DSL06-1LZ	Best	1	6	
			Skylark	CTCL-153	Best	1	6	
			Diva	DVCL-153PL	Best	1	6	Fully extinguished by 20%
CFL/LED	Lutron		Maestro	MACL-153MLH	Best	1	6	
			Skylark	SCL-153P	Best	1	6	
			Toggler	TGCL-153PH	Best	1	6	
			Radio RA	RA2RR-6CL-PD	Best	1	6	
			Harmony	DCL453-PTC	Best	1	6	
	Legrand		Harmony	HCL453PTC	Good	1	6	Not smooth (gets randomly brighter in the middle with all quantitie
		Х	Adorne Paddle	ADPD453LM2	Best	1	6	Dims to 2%
	Leviton	у	Vizia	VPE04	Best	1	6	
			IllumaTech	IPE04	Bad	1	6	Not smooth while adjusting. Slight flicker at most levels
		88	Decora	6615-P	Bad	1	6	Not smooth while adjusting. Slight flicker at most levels
			Skylark Countour	CTELV-303P	Best	1	6	, , ,
Electronic Low Voltage	Lutron		Diva	DVELV-300P	Best	1	6	
		ad	Maestro	MAELV-600	Best	1	6	
			Skylark	SELVB-300P	Best	1	6	
			VIERTI	VTEL-600M-W	Best	1	6	
	Legrand	ag	Scene Director	SCELV	Best	1	6	
			Vizia	VPM-06	Good	1	6	Slight flicker while adjusting. No flicker when stationary
	Leviton		Decora	6613-P	Best	1	6	LE dead travel (20%)
Magnetic Low Voltage	Lutron		Maestro	MALV-600	Not Compatible	-	6	LL dead traver (20%)
wagnetic tow voltage	Lutron Legrand			DLV703-PW	Best	1	6	Fully optinguished @ 209/
			Harmony Titan	CDLV703-PW	Best	2	6	Fully extinguished @ 20%
			Пап	ICDEV/03-PW	Bau		0	Not smooth with 1, significant delay when ↑ from MIN
	Leviton	am	Decora Digital (Bluetooth)	DDMX1-BLZ	Good	1	6	Not perfectly smooth, but stable
	Leviton		Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	, , , , , , , , , , , , , , , , , , , ,
	Leviton		Decora Smart WiFi Technology	DW1KD	Best	1	6	
Smart Dimmer	Lutron		Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	
								D: 1.0%
	Lutron	_	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dims to 3%
	GE	ar	Z WAVE	ZW3005	Best	1	6	Very slight flicker WHILE DIMMING at low levels
Universal	Legrand	1 80	Adorne SofTap	ADTP703TU	Best	1	6	
			Miro Decorator	DRD4-W	Not Compatible		6	
			Harmony	H703PTUTC	1407 Compatible	1	6	Not smooth. Not compatible with 1
	Legranu		Adorne Whisper	ADWR700MMTUW2	Best	1	6	Not smooth. Not compatible with 1
			Adorne Touch	ADTH700MMTUM2	Best	1	6	
				IUD I LI LOOININI I OINIZ	Desi		0	
		_		DALCOD CO 1/ 1	Б.		_	ALL COLORS
	Cooper	ах	Decorator Skye	DAL06P-C2-K-L SAL06P-W-K-L	Bad	1	6	Not compatible with >4.

\*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

·							
Description							
One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.							
One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.							
One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.							
Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBa), wide dimming range - can dim down to 20% or less of light output.							
Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.							

Contact Information:

Builbrite industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@builbrite.com
2/2017 Builbrite Industries Inc.
All Rights Reserved.