



- 17W LED 9IN FLUSH MOUNT 5CCT WHITE DIMMABLE JA8
Item #773611
Ordering Code LED17FLUSH/9/5CCT/927-950/J/WH/D
UPC 739698736112
- Surface mounted 9" LED Flush Mount in white, black, and nickel
 - Easy installation via mounting bracket to J-Box, included mounting bracket compatible with 5", 7" and 9" flush mount
 - High light output, 5CCT Selectable (2700K/3000K/3500K/4000K/5000K)
 - Ideal for residential bedrooms, living rooms, bathrooms, laundry rooms, offices or family rooms



TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)
773611	17	9" FLUSH MOUNT E26		120	White	110	5 CCT - 27/30/35/40/50K
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent
#N/A	90	1400	N/A	50000	9	0.73	90
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating Type	Enclosed Rated	Dimmable	Warranty
N	N	Y	UL	WET	N	Y	5

Order Multiple
QTY
10

APPLICATION SUGGESTIONS





840 Drop Off Drive, Suite A
Summerville, SC 29486

Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment. Actual results may vary.

Product Family Name:

Item Number: 773611

Ordering Code: LED17FLUSH/9/5CCT/927-950/J/WH/D

Item Number:

Ordering Code:

	Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes
					Recommended Minimum	Maximum Tested*	
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Leviton	a IllumaTech	IPI06	Not Compatible		6	
		b SureSlide	6633-P	Bad	1	6	Flickers, not compatible with 6
		c Vizia	VPI06-1LZ	Good	1	6	Slight flicker with 6
	Lutron	d Toggler	TG-600	Good	1	6	Slight flicker, not smooth
		e Lumea	LGCL-600	Good	1	6	Not smooth, slight delay in operation
		f Diva	DV-600	Best	1	6	
		g Skylark	S-600	Good	1	6	Not smooth, slight flicker while adjusting
		h Maestro	MAW-600	Not Compatible	2	6	Not compatible with <2, poor operation 2 or more
	Legrand	i Titan	CD703-PW	Bad	2	6	Not compatible with <2
		j Harmony	D703-PTC	Bad	2	6	Not compatible with <2
		k Harmony	H703-PTC	Bad	2	6	Not compatible with <2, not smooth
CFL/LED	Leviton	l IllumaTech	IPL06	Good	1	6	HE dead travel (10%), significant delay when ↑ from MIN
		m Sureslide	6674	Best	1	6	
		n Decora	6672	Best	1	6	
		o Decora Slide	DSL06-1LZ	Best	1	6	HE dead travel (20%)
	Lutron	p Skylark	CTCL-153	Best	1	6	
		q Diva	DVCL-153PL	Best	1	6	
		r Maestro	MACL-153MLH	Best	1	6	Dims to 2%
		s Skylark	SCL-153P	Best	1	6	
		t Toggler	TGCL-153PH	Best	1	6	
		u Radio RA	RA2RR-6CL-PD	Best	1	6	
	Legrand	v Harmony	DCL453-PTC	Best	1	6	Dims to 1%
		w Harmony	HCL453PTC	Good	1	6	Not smooth (gets randomly brighter in the middle with all quantities)
		x Adorne Paddle	ADPD453LM2	Best	1	6	Dims to 3%
Electronic Low Voltage	Leviton	y Vizia	VPE04	Best	1	6	
		z IllumaTech	IPE04	Bad	1	6	Not smooth while adjusting. Slight flicker at most levels
	Lutron	aa Decora	6615-P	Good	1	6	Slight flicker at most levels. HE dead travel (20%)
		ab Skylark Countour	CTELV-303P	Best	1	6	
		ac Diva	DVELV-300P	Best	1	6	
		ad Maestro	MAELV-600	Best	1	6	
		ae Skylark	SELVB-300P	Best	1	6	
		af VIERTI	VTEL-600M-W	Best	1	6	
		ag Scene Director	SCELV	Good	1	6	Slight flicker while adjusting.
Magnetic Low Voltage	Leviton	ah Vizia	VPM-06	Bad	1	6	Slight flicker while adjusting. Some flicker when stationary
		ai Decora	6613-P	Best	1	6	LE dead travel (20%)
	Lutron	aj Maestro	MALV-600	Not Compatible		6	
		ak Harmony	DLV703-PW	Bad	1	6	Not compatible with 1, not smooth, significant delay
	Legrand	al Titan	CDLV703-PW	Bad	2	6	Not compatible with 1, significant delay when ↑ from MIN
Smart Dimmer	Leviton	am Decora Digital (Bluetooth)	DDMX1-BLZ	Best	1	6	
	Leviton	an Decora Smart Z-Wave Technology	DZ6HD	Best	1	6	
	Leviton	ao Decora Smart WiFi Technology	DW1KD	Best	1	6	
	Lutron	ap Caseta Wireless smart dimmer Wi-Fi	PD-10NXD	Best	1	6	
	Lutron	aq Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Bad	1	6	Dims to 4%, not smooth, flickers while adjusting, flickers at LOW
	GE	ar Z WAVE	ZW3005	Good	1	6	Slight flicker while dimming at low levels, slight flicker at most levels
Universal	Legrand	as Adorne SoftTap	ADTP703TU	Bad	2	6	Not compatible with 1
		at Miro Decorator	DRD4-W	Best	1	6	
		au Harmony	H703PTUTC	Not Compatible	5	6	Not smooth. Not compatible with <5
		av Adorne Whisper	ADWR700MMTUM2	Best	1	6	
		aw Adorne Touch	ADTH700MMTUM2	Good	1	6	Very slight flicker at MAX
	Cooper	ax Decorator	DAL06P-C2-K-L	Bad	1	6	Not compatible with <4.
		ay Skye	SAL06P-W-K-L		1	6	

*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.

†May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

Overall Rating	Description
Not Compatible	One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.
Bad	One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.
Good	One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.
Best	Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.
High End (HE) Dead Travel Low End (LE) Dead Travel	Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.

Contact Information:

Bulbrite Industries Inc.
145 West Commercial Avenue
Moonachie, New Jersey 07074
PHONE: 1-800-528-5555
FAX: 1-800-441-7708
Email: ProductSupport@bulbrite.com
©2017 Bulbrite Industries Inc.
All Rights Reserved.