

DesignLights Consortium



Model Number	PLTM941142
Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	34 W
Reported Light Output	4420 lm
Reported CCT	3500 K
Reported CRI (Ra)	82
Product ID	S-KT9FZ6
DLC Family Code	EMWCCB
Listing Status	Listed
Date Qualified	2025-02-20

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-KT9FZ6
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTM941142
Parent	Yes
Classification	Standard
DLC Family Code	EMWCCB
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No
Sensor Type	No
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4420 lm
Reported Efficacy (AC)	130 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	6
Reported IES Rf	83
Reported IES Rg	98
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3400 lm
Reported Maximum Light Output	4420 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4420 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	34 W
Reported Total Harmonic Distortion	10.7 %
Reported Power Factor	0.965
Reported Minimum Input Wattage	25 W
Reported Maximum Input Wattage	34
Reported Default Input Wattage	34 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
-------------------------------------	-----

Tested Light Output	4789 lm
Tested Efficacy (AC)	134.84 lm/W
Tested CCT	3420 K
Tested CRI (Ra)	82
Tested R9	5
Tested IES Rf	83
Tested IES Rg	98
Tested IES Rcs,h1	-12 %
Tested Duv	0.0008

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	35.5 W
Tested Total Harmonic Distortion	10.7 %
Tested Power Factor	0.965

VERSION HISTORY VIEW DETAILS

2025-02-20	Listed	5.1	Standard
------------	--------	-----	----------