

DesignLights Consortium



| | |
|------------------------|--|
| Model Number | SFLD-15-CS-U-BZ-PC |
| Classification | Premium |
| Primary Use | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires |
| Reported Input Wattage | 15 W |
| Reported Light Output | 1903 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 81 |
| Product ID | S-WHD0QV |
| DLC Family Code | SLFDAL |
| Listing Status | Listed |
| Date Qualified | 2024-06-12 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|-----------------------------|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-WHD0QV |
| Manufacturer | Halco Lighting Technologies |
| Brand | Halco |
| Model Number | SFLD-15-CS-U-BZ-PC |
| Parent | Yes |
| Classification | Premium |
| DLC Family Code | SLFDAL |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|--|
| Category | Outdoor Luminaires |
| General Application | Low Output |
| Primary Use Designation | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires |

CONTROL FEATURES VIEW DETAILS

| | |
|--|------------------------------------|
| Integral Controls | No |
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No |
| Sensor Type | No |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No |
| Field Adjustable Light Output | No |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|-------------|
| Reported Light Output | 1903 lm |
| Reported Efficacy (AC) | 127.22 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 81 |
| Reported R9 | 1 |
| Reported IES Rf | 83 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -12 |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 1903 lm |
| Reported BUG Rating | B2 U0 G0 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 15 W |
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 15 W |
| Reported Maximum Input Wattage | 15 |
| Reported Default Input Wattage | 15 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|---|---|
| Tested Voltage for Minimum Efficacy | 120 |
| Tested Light Output | 1903 lm |
| Tested Efficacy (AC) | 127.22 lm/W |
| Tested CCT | 2975 K |
| Tested CRI (Ra) | 81 |
| Tested R9 | 1 |
| Tested IES Rf | 83 |
| Tested IES Rg | 96 |
| Tested IES Rcs,h1 | -12 % |
| Tested Duv | 0.0005 |
| Field Adjustable Light Distribution Setting | Diffuser light angle=90/75/55 deg, pointing Straight down |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|----------------------------------|-------|
| Tested Input Wattage | 15 W |
| Tested Total Harmonic Distortion | 5 % |
| Tested Power Factor | 0.992 |

VERSION HISTORY VIEW DETAILS

| | | | |
|------------|--------|-----|---------|
| 2024-06-12 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|