DesignLights Consortium





Model Number	PLTSPP321111
Classification	Premium
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	50 W
Reported Light Output	6250 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	S-FFK3MT
DLC Family Code	SLFHGL
Listing Status	Listed
Date Qualified	2025-02-17

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-FFK3MT
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT
Model Number	PLTSPP321111
Parent	No
Classification	Premium
DLC Family Code	SLFHGL
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	Troffer	
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces	

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes	
Dimming Capability and Range	Continuous Dimming above 10%	
Integral Control Capability	Energy Monitoring, High End Trim, LLLC	
Sensor Type	Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing	
SSL V5 Wired Communication Protocol	0-10V Analog, Phase Cut	
SSL V5 Wireless Communication Protocol	Bluetooth	
Field Adjustable Light Output	Yes	
White-Tunable	Yes	
Warm-Dimming	No	
Field Adjustable Light Distribution	No	

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	6250 lm
Reported Efficacy (AC)	125 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	0
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-11
Reported Minimum Light Output	3750 lm
Reported Maximum Light Output	6250 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	6250 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	50 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	30 W
Reported Maximum Input Wattage	50
Reported Default Input Wattage	50 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2025-02-17	Listed	5.1 Premium	
------------	--------	-------------	--