



DESCRIPTION

Quickly and easily add lights to shelves, display cases, and more with these 3000K LED tape lights and compatible accessories.

FEATURES

- High color rendering index of 90 makes color appear brighter and more accurate
- Can be cut in 4-inch increments; cutting points are noted on the tape light
- 24V constant current drivers, controllers, and other accessories sold separately; see Suggested Accessories section for list of compatible accessories
- Parylene Nano coating, is completely transparent and weather resistant
- Maximum run is 16 feet
- Adhesive 3M tape backing

LISTINGS

- UL Listed
- CE
- IP65 (tape light when uncut)
- Enclosed Rated

PERFORMANCE

- CRI: 90+
- CCT: 3000K
- LED L70 Life Hours: 25,000 hours

WARRANTY

- 2-year limited warranty; see pltsolutions.com for warranty details

Project name	Type
Catalog number	
Comments	Voltage
Approved by	Date



APPLICATIONS

- Display Cases
- Covers
- Under Cabinets
- Shelves
- Staircase Steps

TAPE LIGHT	Wattage Per Foot	3.5
	Lumens Per Foot	260
	CRI	90
	CCT	3000K
	LED L70 Life Hours	25,000
	Voltage	24V
LISTINGS	Adhesive Backing	3M
	Certifications	UL Listed; CE; IP65
	Environment	Indoor/Dry Location; Enclosed Rated

PERFORMANCE SUMMARY

Item #	Wattage Per Foot	Lumens Per Foot	Voltage	CCT	CRI	Cutting Intervals	LED L70 Life Hours	Dimmable
FLX-00105	3.5	260	24V	3000K	90	4"	25,000	Yes

ACCESSORIES

SKU	Description
FLX-FY2402500	Power Supply for 24 Volt LED Tape Light - 60 Watt Max - 120 Volt Input
FLX-CAP2S4P12IN	Power Cord Connector - 12 in. - for 12V or 24V LED Tape Light

DIMENSIONS

DIMENSIONS:

Height - 0.1"

Width - 0.44"

Length - 16'

WARNINGS

- LED tape light is IP65 rated only when left uncut. Once cut, it is dry location only.
- Not for use underwater.
- Drivers can only operate up to 16' (or one spool) of tape light.
- FLX-CAP2S4P12IN is not for use with RGB tape light