



Model Number	PLTSN1D211[1;2;3]1[1;2;Blank][1;2;Blank]
Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	241.4 W
Reported Light Output	32616 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	S-H17899
DLC Family Code	VXHPKC
Listing Status	Listed
Date Qualified	2025-06-03

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-H17899
Manufacturer	Precision Lighting & Transformer, Inc
Brand	PLT Solutions
Model Number	PLTSN1D211[1;2;3]1[1;2;Blank][1;2;Blank]
Parent	No
Classification	Premium
DLC Family Code	VXHPKC
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	LLLC
Sensor Type	Sensor Receptacle, Daylight Sensing, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	Bluetooth
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	32616 lm
Reported Efficacy (AC)	135.14 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	10
Reported IES Rf	84
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Minimum Light Output	16217 lm
Reported Maximum Light Output	32616 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	32616 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	241.4 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	120 W
Reported Maximum Input Wattage	241.4
Reported Default Input Wattage	241.4 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Pointing Straight down at 60 deg beam angle setting
---	---

VERSION HISTORY VIEW DETAILS

2025-06-03	Listed	5.1	Premium
------------	--------	-----	---------